

Purple Wind

Owner's Manual

Purple Wind is a 5W Class AB Guitar Amplifier Head

Features

- Sound based on legendary Marshall Plexi SuperLead 1959 (Limited Edition)*
- Extremely compact configuration for portability
- High quality tone with Volume and Gain controls
- 3 Band EQ controls for shaping your tone
- FX LOOP for using external effects
- Speaker out can automatically fit different cabinets of different impedance (4-16 Ω)
- Headphone/line output jack is very convenient for practicing and recording
- Aux in jack can let you play with the external music player

* Marshall Plexi Super Lead 1959 is an amplifier model of Marshall Amplification plc., the mentioned manufacturer and product names are trademarks or registered trademarks of their respective owners, the trademarks were used merely to identify the sound character of this product

Panel Instructions



Front

- 1.INPUT: 1/4" mono jack, plug in your guitar.
- 2.BASS: Control the low frequency response.
- 3.MIDDLE: Control the mid frequency response.
- 4.TREBLE: Control the high frequency response.
- 5.GAIN: Control the gain level.
- 6.VOLUME: Control the output volume.

Back

- 1 18V DC: Plug in 18V DC adapter (center negative).
- 2 PHONES/LINE OUTPUT: 1/8" stereo jack, for using headphones or recording.
- 3 AUX IN: 1/8" stereo jack, for connecting an external music player.
- 4 FX LOOP SEND: 1/4" mono jack, send the signal to the Input jack of the connected effect unit (The Effects Loop is a patch point between the pre-amp and power amp).
- 5 FX LOOP RETURN: 1/4" mono jack, connect to the Output jack of the connected effect unit.
- 6 SPEAKER OUTPUT: 1/4" mono jack, for connecting to the cabinet (speaker 4-16 Ω).



Specifications

Power Output: 5 Watts

Dimensions: 128 mm(W) x 75 mm(D) x 59.5 mm(H)

Weight: 440 g

Structure Design Patent Pending
Appearance Design Patent Pending