SMT25 THE ULTIMATE RIM-MOUNT GOOSENECK MIC HOLDER

OVERVIEW

The MST25 is a professional, simple to use shockmount sustem that attaches to any standard microphone tand with either 3/8" or 5/8" threads. the SMT25 is provided with a 3/8" threaded inset that allows it to be used with European-style mic stands. To use with 5/8" mic stands, simply remove the adapter.

Optimized for use with a wide variety of microphones, the SMT25 will work with microphones having an OD (outer diameter) of .82" - 1.06" / 21 mm - 27 mm.

TO OPERATE

The microphone is held in place by the foam lined metal housing in the center of the shockmount. To open up the diameter and insert microphone, squeeze the two metal clips together between your thumb and fingers. (see Fig. 1)

The wingnut located at the bottom of the clip (see Fig. 2) will control the rotation of the shockmount 180 degrees. Simply loosen (counter-clockwise) or tighten (clockwise) the wingnut as needed.



The SMt25 is ideally suited for instrument condenser microphones such as the ADX51, SCX1 and SCX25a — and a wide variety of other popular microphones on the market. The SMT25 will hold the microphone securely in just about any position. With condenser microphones, it is important that the element and all ports in the housings and grills remain completely exposed.

VOCAL MICROPHONES

The SMT25 will also work with vocal microphones such as the OM series and the VX4 (pictured), and a wide variety of other popular microphones on the market. Since vocal microphones tend to be larger in diameter (24-25mm on the average) they may take a bit more finesse to intall. The mic may have to be worked into the housing by carefully twisting the mic back and forth as you are pushing into position.



FEATURES

- · Provides maximum isolation from vibration
- Heavy duty shock cord
- Metal wingnut locks holder into desired position
- Works with a wide variety of popular microphones
- Tension fit holds microphone firmly in place



FIG. 1: Squeeze together the metal clips to open up the diameter of the center metal tube.



FIG. 2: Wingnut will rotate the position of the shockmount 180 degrees.



FIG. 3: VX-5 vocal microphone

SMT25

 $\textbf{PRODUCT REGISTRATION:} \ Please \ register \ your \ product \ online \ at \ www.audixusa.com/docs_12/about/product_registration.shtml.$

SERVICE AND WARRANTY: This product is under warranty for a period of 1 year to be free of defects in material and workmanship. In the event of a product failure due to materials or workmanship, Audix will repair or replace said product at no charge with proof of purchase. Audix does not pay or reimburse shipping costs for warranty repairs or returns. The warranty excludes any causes other than manufacturing defects, such as normal wear, abuse, environmental damage, shipping damage or failure to use or maintain the product per the supplied instructions. No Implied Warranties: All implied warranties, including but not limited to implied warranties of merchantability and fitness for a particular purpose are hereby excluded. The liability of Audix, if any, for damages relating to allegedly defective products shall be limited to the actual price paid by Dealer for such products and shall in no event include incidental or consequential damages of any kind. Should your product fail in any way, please contact the Audix Service department at 503.682.6933. A Return Authorization is required before returning any product. OTHER THAN THIS WARRANTY, AUDIX MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE PRODUCTS, THE USE OF THE PRODUCTS, THE PERFORMANCE OF THE PRODUCTS. AUDIX SHALL NOT BE LIABLE FOR SPECIAL INCIDENTAL, CONSEQUENTIAL, INDIRECT OR SIMILAR DAMAGES ARISING FROM OR BASED ON THE SALE, USE, STORAGE OR DISPOSAL OF THE PRODUCTS, AUDIX'S SERVICE WORK, BREACH OF WARRANTY, BREACH OF CONTRACT. NEGLIGENCE, OR ANY OTHER THEORY OF LIABILITY, EVEN IF AUDIX HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.