



COLORADO™ 1VW



Full Cool



50/50 Mix



Full Warm

CONTROL FEATURES

- 2, 3, or 6-channel LED wash light (with ID addressing)
- Operating modes
 - 2-channel: master dimmer, color temp macros
 - 2-channel: cool white, warm white control
 - 3-channel: cool white, warm white, dimmer
 - 6-channel: master dimmer, cool white, warm white, color temp macros, strobe, ID addressing
- Color temp mixing with or without DMX controller
- Recall custom programs via master/slave or DMX

ADDITIONAL FEATURES

- High power, 1 W (350 mA) LEDs
- Ingress Protection: IP66
- Additional power output: max 20 units @ 120 V (see manual for details)
- LED display with password protection
- Gel frame holder (4 mm max thickness)
- Recall custom programs between fixtures
- Double-bracket yoke doubles as floor stand

OPTIONS

- Optical system: 30° (installed)
- 16.4 ft (5 m) power extension cable (IP5POWER)
- 16.4 ft (5 m) signal extension cable (IP5SIG)

SPECIFICATIONS

- 15° optics
- Beam angle: 17.4°
- Field angle: 42.2°
- Lux: 2,058.39 @ 2 m
- Light source: 36 1 W (18 x 350 mA warm, 18 x 350 mA cool white) LEDs, 50,000 hrs
- Power and current: 120 V, 60 Hz; 50.4 W, 0.7 A (operating), 0.4 A (inrush)
- AC power: Auto-ranging 100 V ~ 240 V 50/60 Hz
- Power cable with plug: 65 in (1,651 mm)
- IP66 power extension cable: 103 in (2,604 mm)
- IP66 signal extension cable: 103 in (2,604 mm)
- DMX input cable: 6.5 in (165 mm)
- DMX output cable: 6.5 in (165 mm)
- Weight: 9.5 lbs / 4.3 kg
- Size: 7.9 x 9.5 x 9.6 in / 200 x 243 x 244 mm

www.chauvetlighting.com
 info@chauvetlighting.com
 t: 954.929.1115
 3000 North 29th Court
 Hollywood, FL 33020

CHAUVET®