

COLORdash™ Par



CONTROL FEATURES

- 3, 4, or 9-channel RGB wash light
- Operating modes
 - 3-channel: RGB control
 - 4-channel: RGB, dimmer
 - 9-channel: RGB, ID addressing, dimmer, macro, strobe, auto / custom
- RGB color mixing with or without DMX controller
- Built-in automated programs via master/slave or DMX
- Program and recall custom programs via master/slave or DMX

ADDITIONAL FEATURES

- Additional threaded hole on rear for mounting (size M 10)
- Additional (IEC) power output: max 20 units @ 120 V
- Includes 6.6 ft (2 m) power extension cable
- LCD display with password protection
- Adjustable barn doors to direct output (includes gel frame)
- Transfer custom programs between fixtures
- Double-bracket yoke doubles as floor stand

SPECIFICATIONS

- Installed optics: 15° Optional optics 30°
Beam angle: 12° Beam angle: 28°
Field angle: 26° Field angle: 55°
Lux: 1,270 @ 2 m Lux: 349 @ 2 m
- Light source: 18 x 1 W LEDs, 50,000 hrs
(6 x 350 mA red, 6 x 350 mA green, 6 x 350 mA blue)
- Power and current: 120 V, 60 Hz; 24.6 W, 0.4 A (operating), 0.3 A (inrush)
230 V, 50 Hz; 26 W, 0.3 A (operating), 0.3 A (inrush)
- AC power: Auto-ranging 100 V ~ 240 V 50/60 Hz
- IEC power cable with plug: 60 in (1,524 mm)
- IEC power Linking cable: 82 in (2,083 mm)
- Weight: 5.8 lbs / 2.6 kg
- Size: 6.2 x 8.2 x 9.3 in / 157 x 208 x 237 mm

OPTIONS

- Optical systems: 30° (CL20X30)

www.chauvetlighting.com
info@chauvetlighting.com
t: 954.929.1115
3000 North 29th Court
Hollywood, FL 33020

CHAUVET[®]
Value • Innovation • Performance