

## Specification

Nominal Basket Diameter	12", 304.8mm
Nominal Impedance*	8 ohms
Power Rating**	225W
Resonance	45Hz
Usable Frequency Range***	48Hz-8kHz
Sensitivity	97.7
Magnet Weight	38 oz.
Gap Height	0.312", 7.92mm
Voice Coil Diameter	2", 50.8mm

## Thiele & Small Parameters

Resonant Frequency (fs)	45Hz
DC Resistance (Re)	7.37
Coil Inductance (Le)	0.83mH
Mechanical Q (Qms)	6.44
Electromagnetic Q (Qes)	0.55
Total Q (Qts)	0.51
Compliance Equivalent Volume (Vas)	136.3 liters / 4.8 cu. ft.
Peak Diaphragm Displacement Volume (Vd)	170cc
Mechanical Compliance of Suspension (Cms)	0.34mm/N
BL Product (BL)	11.7 T-M
Diaphragm Mass inc. Airload (Mms)	36 grams
Efficiency Bandwidth Product (EBP)	82
Maximum Linear Excursion (Xmax)	3.2mm
Surface Area of Cone (Sd)	532.4 cm <sup>2</sup>
Maximum Mechanical Limit (Xlim)	8.0mm

## Mounting Information

Recommended Enclosure Volume	
Sealed	14-51 liters/0.5-1.8 cu.ft.
Vented	56.6-116 liters/2-4.1 cu.ft.
Overall Diameter	12.03", 305.5mm
Baffle Hole Diameter	10.95", 278.1mm
Front Sealing Gasket	fitted as standard
Rear Sealing Gasket	fitted as standard
Mounting Holes Diameter	0.25", 6.4mm
Mounting Holes B.C.D.	11.59", 294.3mm
Depth	4.47", 114mm
Net Weight	8.1 lbs., 3.7 kg
Shipping Weight	10.2 lbs., 4.6 kg

## Materials of Construction


Copper voice coil  
Polyimide former  
Ferrite magnet  
Vented core  
Pressed steel basket  
Paper Cone  
Cloth cone edge  
Solid composition paper dust cap

  
**EMINENCE®**  
The Art and Science of Sound



## BETA-12LTA American Standard Series

Recommended for professional audio as a woofer in small sealed monitor, or as a PA woofer or monitor in a vented enclosure.



\* Please inquire about alternative impedances.

\*\* Multiple units exceed published rating evaluated under EIA 426A noise source and test standard while in a free-air, non-temperature controlled environment.

\*\*\* The average output across the usable frequency range when applying 1W/1M into the nominal impedance. ie: 2.83V/8ohms, 4V/16ohms.

Eminence response curves are measured under the following conditions: All speakers are tested at 1w/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2ft. X 2ft. baffle is built into the wall with the speaker mounted flush against a steel ring for minimum diffraction | Hafler P1500 Trans-Nova amplifier | 2700 cu.ft. chamber with fiberglass on all six surfaces (three with custom-made wedges)